

Société	
Créé par	
Date	



Fluid	
Fluid temperature (°C)	
Ambient temperature (°C)	
Fluid pressure (bar)	
Maximum admissible pressure drop (bar)	
Required flow rate (m³/h)	
Threaded connection	
Valve scheme	<input type="checkbox"/> 2/2 NO <input type="checkbox"/> 2/2 NC <input type="checkbox"/> 3/2 NO <input type="checkbox"/> 3/2 NC
Operating type	<input type="checkbox"/> Direct <input type="checkbox"/> Servo-assisted <input type="checkbox"/> Mixed
Body material	<input type="checkbox"/> Brass <input type="checkbox"/> Stainless steel
Gasket material	<input type="checkbox"/> NBR <input type="checkbox"/> EPDM <input type="checkbox"/> PTFE <input type="checkbox"/> FKM/FPM
Nominal voltage	<input type="checkbox"/> 12VDC <input type="checkbox"/> 24VDC <input type="checkbox"/> 24V 50/60Hz <input type="checkbox"/> 110V 50/60Hz <input type="checkbox"/> 220V 50/60Hz
Connector type	<input type="checkbox"/> Standard <input type="checkbox"/> LED <input type="checkbox"/> LED+VDR
Application description	
Required quantity	